


UNIVERSAL COLUMNS

Normal Stock to EN10025 S355




Designation		Depth of Section 'D'	Width of Section 'B'	Thickness		Depth between Fillets 'F'
Serial Size mm	Mass per Metre Kg/m	mm	mm	Web 't' mm	Flange 'T' mm	mm
152 x 152	23.0	152.4	152.2	5.8	6.8	123.6
	30.0	157.6	152.9	6.5	9.4	123.6
	37.0	161.8	154.4	8.0	11.5	123.6
203 x 203	46.1	203.2	203.6	7.2	11.0	160.8
	52.0	206.2	204.3	7.9	12.5	160.8
	60.0	209.6	205.8	9.4	14.2	160.8
	71.0	215.8	206.4	10.0	17.3	160.8
	86.1	222.2	209.1	12.7	20.5	160.8
254 x 254	73.1	254.1	254.6	8.6	14.2	200.3
	88.9	260.3	256.3	10.3	17.3	200.3
	107.1	266.7	258.8	12.8	20.5	200.3
	132.0	276.3	261.3	15.3	25.3	200.3
	167.1	289.1	265.2	19.2	31.7	200.3
305 x 305	96.9	307.9	305.3	9.9	15.4	246.7
	117.9	314.5	307.4	12.0	18.7	246.7
	136.9	320.5	309.2	13.8	21.7	246.7
	158.1	327.1	311.2	15.8	25.0	246.7
	198.1	339.9	314.5	19.1	31.4	246.7
	240.0	352.5	318.4	23.0	37.7	246.7
	282.9	365.3	322.2	26.8	44.1	246.7

Standard Mill lengths available also cut to size

Others sizes available

Standard Mill lengths available also cut to size





UNIVERSAL BEAMS

Normal Stock to EN10025 S355

Designation			Depth of Section 'D' mm	Width of Section 'B' mm	Thickness Web 't' mm	Flange 'T' mm	Depth between Filletts 'F' mm
Serial Size mm	Mass per Metre Kg/m						
127 x 76	13.0		127.0	76.0	4.0	7.6	96.6
152 x 89	16.0		152.4	88.7	4.5	7.7	121.80
178 x 102	19.0		177.8	101.2	4.8	7.9	146.8
203 x 102	23.1		203.2	101.8	5.4	9.3	169.4
203 x 133	25.1		203.2	133.2	5.7	7.8	172.4
	30.0		206.8	133.9	6.4	9.6	172.4
254 x 102	22.00		254.0	101.6	5.7	6.8	225.2
	25.2		257.2	101.6	6.0	8.4	225.2
	28.3		260.4	102.2	6.3	10.0	225.2
254 x 146	31.1		251.4	146.1	6.0	8.6	219.0
	37.0		256.0	146.4	6.3	10.9	219.0
	4.30		259.6	147.3	7.2	12.7	219.0
305 x 102	24.8		305.1	101.6	5.8	7.0	275.9
	28.2		308.7	101.8	6.0	8.8	275.9
	32.8		312.7	102.4	6.6	10.8	275.9
305 x 127	37.0		304.4	123.3	7.1	10.7	265.2
	41.9		307.2	124.3	8.0	12.1	265.2
	48.1		311.1	125.3	9.0	14.0	265.2
305 x 165	40.3		303.4	165.0	6.0	10.2	265.2
	46.10		306.6	165.7	6.7	11.8	265.2
	54.0		310.4	166.9	7.9	13.7	265.2
356 x 127	33.1		349.0	125.4	6.0	8.5	311.6
	39.1		353.4	126.0	6.6	10.7	311.6
356 x 171	45.0		351.4	171.1	7.0	9.7	311.6
	51.0		355.0	171.5	7.4	11.5	311.6
	57.0		358	172.2	8.1	13.0	311.6
	67.1		363.4	173.2	9.1	15.7	311.6

Standard Mill lengths available also cut to size

Other sizes available

01209 213171 (Option 1)

steelsales@sjandrew.com

